For Global Market

MaysunSolar

Monocrystalline PV Module

MS(320-340)MB- 60H

9BB

- More uniform current collection ability, reduces the current and heat loss of the battery in the module; beautiful appearance, more suitable for roof installation.
- Using half-piece PERC structure technology (low resistance), the output of mono crystalline 60pcs series is up to 335W (module conversion efficiency is up to 19.85%).
- System voltage 1000V/1500V standard
- It can ensure that the components produced on a large scale can pass the PID (potential induced attenuation) test.
- Excellent performance in low light environment achieved by using excellent surface velveting technology of glass and cells.
- The whole module is certified by 1600Pa wind load and 3600Pa snow load.
- Certified by high salt spray and high ammonia corrosion test

320	325	330	335	340

EN

ELECTRICAL SPECIFICATIONS

STC rated output (P_{mpp})*	320 Wp	325 Wp	330 Wp	335 Wp	340 Wp
PV Module size	1686*1002*35 mm				
Standard sorted output	0/+5 Wp				
Warranted power output STC ($P_{nominal}$)	320 Wp	325 Wp	330 Wp	335 Wp	340 Wp
Rated voltage (V_{mpp}) at STC	33.4 V	33.6 V	33.8 V	34.0 V	34.3 V
Rated current (I_{mpp}) at STC	9.59 A	9.68 A	9.77 A	9.84 A	9.91 A
Open circuit voltage (V_{oc}) at STC	40.9 V	41.1 V	41.3 V	41.5 V	41.7 V
Short circuit current (I_{sc}) at STC	10.15 A	10.20 A	10.31 A	10.36 A	10.42 A
Module efficiency	18.96%	19.26%	19.56%	19.85%	20.15%
Rated output (P_{mpp}) at NOCT	239 Wp	242 Wp	246 Wp	250 Wp	255 Wp
Rated voltage (V_{mpp}) at NOCT	31.4 V	31.6 V	31.8 V	32.0 V	32.2 V
Rated current (I_{mpp}) at NOCT	7.62 A	7.66 A	7.74 A	7.82 A	7.92 A
Open circuit voltage (V_{oc}) at NOCT	37.8 V	38.0 V	38.2 V	38.4 V	38.6 V
Short circuit current (I_{sc}) at NOCT	8.44 A	8.54 A	8.65 A	8.74 A	8.80 A

Temperature coefficient (P_{mpp})	- 0.380%/K
Temperature coefficient (I_{sc})	+0.042%/K
Temperature coefficient (I_{mpp})	- 0.008%/K
Temperature coefficient (V_{mpp})	- 0.373%/K
Temperature coefficient (V_{oc})	- 0.284%/K
Normal operating cell temperature (NOCT)	46±2°C

Maximum system voltage (IEC)	1000V_{DC} / 1500V_{DC}
Number of diodes	3
Maximum series fuse rating	15 A
Operating Temperature	-40℃ to +85℃

* Measurement tolerance +/- 3%

IEC 61701 Salt Spray test Severity (3) | IEC 60068-2-68 Sand test | IEC 62804 1500V PID test

MAYSUN SOLAR

RELATED PARAMETERS

Cell type	Monocrystalline 158.75*158.75
Number of cells / cell arrangement	120 / 6*20
Cells dimension	6"
Packing unit	30 modules
Weight of packing unit (for container)	570kg / 1257 lbs

MECHANICAL SPECIFICATIONS

Outer dimensions (L x W x H)	1686*1002*35mm 66.37 * 39.48 * 1.38 in
Frame technology	Aluminum,silver anodized
Module composition	Glass/EVA/Backsheet(white)
Weight (module only)	19kg /41.88 lbs
Front glass thickness	3.2mm / 0.13 in
Junction box IP rating	IP 65/67
①Cable length(IEC)	300/400mm / 11.81/15.75 in
Cable diameter (IEC)	12 AWG/4mm²
②Maximum load capacity	3600 Pa
Fire performance (IEC)	Class C
Connector type (IEC)	MC4 compatible

Refer to Maysun Solar crystalline installation manual.

QUALIFICATION AND LINEAR WARRANTIES

Product standard	IEC61215, 61730
Extended product warranty	12 years
Output decline 3%/year performance P_{mpp} (STC)	1st year
Output decline 0.7%/year performance P_{mpp} (STC)	2nd~ 25th years

ISC / VOC / Pmax Diagram of curves



I-V Curves of PV module MS 320M-120 at various solar irradiance



MODULE DIMENSION DETAILS

Front view	Side view	Rear view	Frame cross section
			

Maysun Solar FZCO Reserves the right of final interpretation.
Specifica tions and designs included in this datasheet are subject to change without notice.

Website: www.maysunsolar.com

Mayaun Solar 10-2019